



Hydraulic Press Brake CNC Press Brake Machine

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: genuo
- Minimum Order Quantity: 1
- Price: negotiable
- Packaging Details: carton box
- Payment Terms: L/C, T/T, D/P, D/A



Product Specification

- Attributes: Advanced Design Concept, Simple Appearance, Comfortable Operation Human-machine Experience, Special CNC Bending Control System
- Highlight: **CNC Press Brake Bending Machine, Press Brake Bending Machine CNC, CNC Hydraulic Press Brake**

for more products please visit us on genuocnc.com

Product Description

Features

Adhering to advanced design concept, simple appearance, comfortable operation human-machine experience

Special CNC bending control system is fitted with mainframe of the bending machine.

Multi-work-step programming function is able to achieve an automatic operation and continuous positioning of multi-step procedures, as well as an automatic precision adjustment for positions of back gauge stopper and gliding block.

The machine is provided with bend counting function, for a real-time display of processing quantity and power-failure memory of positions of stopper and gliding block, as well as procedures and parameters.

Imported ball bearing lead screw and linear guide rail are used for rear stopper, to ensure the positioning precision of rear stopper, for processing precision of machine to be higher.



Details Images



Optional Controller

Delem DA-50 Touch Series

The DA-50 Touch series press brake controls offer modern compact and versatile solutions for powerful economic press brake applications.

Graphical programming and numerical programming solutions based on state-of-the-art press brake control enable optimal flexibility. Optional DA-60 Touch series



Cybelelec CybTouch 8, 12,15, Switzerland

CybTouch is specifically designed for CNC press brakes. It has an intuitive and vivid color full touch screen and a high integration of functions. Its robust design is available in panel or housing version. Thanks to its large keys, online help, simplified software and many other automatic functions that constantly guide the operator, CybTouch open architecture concept for customer specific functionality assurance. User friendly programming with ease due to the "intuitive programming" concept.

Esautomation S630, S640, S650, Italy

The intelligent heart of software specifically designed for bending is beating in all our VIS-600 and 800 CNCs, thus guaranteeing exceptional performance with every type of processing. Developed ad-hoc according each client's needs, our turn key software allows both 2D and 3D visualization, while optimizing all the bending sequences. Thanks to unique Esautomation's exclusive FLED (Fast Learning Design) philosophy, it greatly simplifies and speed up the machineoperator's work.

High Precision Back-Gauge

The unique and novel ball screw linear guide structure back-gauge ensures high positioning accuracy. Multi-level with movable, adjustable stop fingers. Increased positioning range makes bending more efficient and accurate. Optional function more Complete multiple Axes.



Low Noise Power System

Using Germany Siemens main motor and USA SUNNY gear oil pump guarantee the machine service life and improve the machine working stability. At the same time, the special coupling device also greatly reduces the noise of the machine in the process of running.

Patent Fast Clamps

The whole series adopts GENUO GNSP standard fast holders. Patented rear butterfly hold down device, which can adapt to different types of European-standard, Amada type punches. Compared with the traditional tool holder, it can save more time and improve production efficiency. Safety, anti falling. There are also one button release upgrade style. Automatic hydraulic and pneumatic clamping are optional.





Optional Installation

- *Oil Cooling Unit
- *Light Curtain
- *Laser Protection
- *Front Auto Follow support
- *Bending Robots

Size Chart of Design

Type	Normal force (KN)	Workable length (mm)	Poles distance (mm)	Throat depth (mm)	Ram Strokes (mm)	Height of table (mm)	Die loading height (mm)	Power (KW)	Compensation	Axes	Back-Gauge Range (mm)	Dimension L*W*H (mm)	Weight (kg)
WE67K-40T/1250	400	1600	1520	300	150	750	380	4	0	3+0	10-500	1900*1650*2300	2850
WE67K-40T/1600	400	1600	1520	300	150	750	380	4	1	3+1	10-500	2100*1650*2100	3500
WE67K-63T/2500	630	2500	2020	300	150	780	400	5.5	2	3+1	10-600	3100*1700*2300	4800
WE67K-63T/3200	630	3200	2520	320	150	850	400	5.5	3	3+1	10-600	3600*1800*2350	5700
WE67K-80T/2500	800	2500	2020	300	180	780	450	7.5	2	3+1	10-600	3100*1750*2300	5600
WE67K-80T/3200	800	3200	2520	320	180	850	450	7.5	3	3+1	10-600	3600*1750*2350	6900
WE67K-100T/2500	1000	2500	2100	350	200	780	460	7.5	2	3+1	10-600	3200*1850*2400	6800
WE67K-100T/3200	1000	3200	2520	400	200	850	460	7.5	3	3+1	10-600	3900*1850*2450	8300
WE67K-100T/4000	1000	4000	3300	400	200	890	460	7.5	4	3+1	10-600	4700*1900*2550	9500
WE67K-125T/2500	1250	2500	2100	350	200	850	460	7.5	2	3+1	10-600	3200*1900*2550	6900
WE67K-125T/3200	1250	3200	2600	400	200	890	460	11	3	3+1	10-600	3900*1900*2550	8600
WE67K-125T/4000	1250	4000	3300	400	200	890	460	11	4	3+1	10-600	4700*1950*2550	9600
WE67K-125T/5000	1250	5000	4200	400	200	900	460	11	5	3+1	10-600	5600*1950*2550	11500
WE67K-160T/3200	1600	3200	2600	400	220	840	480	11	3	3+1	10-600	4500*1950*2600	8900
WE67K-160T/4000	1600	4000	3300	400	220	840	480	11	4	3+1	10-600	4600*1950*2600	12000
WE67K-160T/5000	1600	5000	4200	400	220	850	480	11	5	3+1	10-600	5600*2000*2650	15000
WE67K-160T/6000	1600	6000	5300	400	220	890	480	15	6	3+1	10-600	6800*2000*2900	17700
WE67K-200T/3200	2000	3200	2600	400	250	900	530	15	3	3+1	10-800	4000*2100*2900	11500
WE67K-200T/4000	2000	4000	3300	400	250	900	530	18.5	4	3+1	10-800	4600*2100*2900	14600
WE67K-200T/5000	2000	5000	4200	400	240	940	530	18.5	5	3+1	10-800	5600*2200*3000	18000
WE67K-200T/6000	2000	6000	5300	400	250	950	530	18.5	6	3+1	10-800	6800*2200*3100	21000
WE67K-250T/3200	2500	3200	2600	400	250	840	530	15	3	3+1	10-800	4100*2200*3000	14600
WE67K-250T/4000	2500	4000	3300	400	250	900	530	22	4	3+1	10-800	5000*2200*3000	16500
WE67K-250T/5000	2500	5000	4200	400	250	940	530	22	5	3+1	10-800	5900*2300*3100	21000
WE67K-250T/6000	2500	6000	5300	400	250	950	530	22	6	3+1	10-800	6900*2300*3500	26000
WE67K-300T/3200	3000	3200	2600	450	300	950	580	22	3	3+1	10-1000	4100*2000*3500	16000
WE67K-300T/4000	3000	4000	3300	450	300	1000	580	22	4	3+1	10-1000	5000*2000*3500	19000
WE67K-300T/5000	3000	5000	4200	450	300	1050	580	22	5	3+1	10-1000	5900*2200*3600	24000
WE67K-300T/6000	3000	6000	5300	450	300	1100	580	22.5	6	3+1	10-1000	6900*2300*3700	26000
WE67K-400T/3200	4000	3200	2600	500	300	1000	580	22.5	4	3+0	10-999	4200*2300*3900	24000
WE67K-400T/4000	4000	4000	3500	500	300	1050	580	22.5	4	3+1	10-1000	5100*2500*3700	28000
WE67K-400T/5000	4000	5000	4400	500	300	1100	580	22.5	5	3+1	10-1000	6000*2500*3900	34000
WE67K-400T/6000	4000	6000	5500	500	300	1200	580	22.5	6	3+1	10-1000	7000*2600*4000	40000

Hot Tags: hydraulic press brake, China, suppliers, manufacturers, factory, price, cost, cheap, for sale, cnc hydraulic press brake, hand press bending machine, plate bending machine, pvc bending machine, press brake bending, 3 in 1 press brake



Maanshan Genuo Machinery Manufacturing Co., Ltd.



0086 555 7168598



sales@genuogroup.com



genuocnc.com

Wanda Center 1116, Yushan District, Maanshan, Anhui, China 243000